



# VIBRATORY ROLLER PAVER COMPACTOR





- 1 **Folding handle for transport and storage convenience.** The handle then acts as engine protection during transport
- 2 **Durable rack and pinion throttle lever.** Very smooth operation and stay-in-place settings. This lever is repairable thereby reducing maintenance costs
- 3 **HONDA GX160**, a proven, dependable power source
- 4 **Rubber coated rollers** protect the pavers. Smooth travel over the pavers without chipping the corners and scuffing the paver surface
- 5 **Lifting handles** for easy loading and unloading
- 6 **Included lifting bail** provides a secure lifting point



MODEL	EVPC120
DIMENSIONS (LxWxH) - in (mm)	41.9 x 26.3 x 42.9 (1,064 x 669 x 1,091)
OPERATING WEIGHT - lbs (kg)	271 (123)
PLATE SIZE (LxW) - in (mm)	25.8 x 24.4 (655 x 620)
VIBRATION FREQUENCY v.p.m. (Hz)	5,640 (94)
CENTRIFUGAL FORCE lbs (kg)	2,315 (1,050)
COMPACTED AREA ft²/h (m²/h)	6,458 - 7,534 (600 – 700)
MAX. GRADEABILITY - °	0.8 (3.1)
RUNNING TIME - hours	1.7
ENGINE	HONDA GX160
ENGINE TYPE	4-STROKE GASOLINE
MAX. POWER OUTPUT - kW (hp)	4.8 (3.6)

1-800-417-9272 | [ezgmfg.com](http://ezgmfg.com)  
 1833 North Riverview Road  
 Malta, OH | 43758

